





MINI SERIES





CHOGORI USA

MINI Series Specifications

Mini Series , Male connector & Female pin

Description	Molded, 180° Lock Bayonet Type, Solder	Molded, 180° Screw Type, Solder
Figure		

Drawing		
---------	---	--

Part-No.	Contacts	Cable Range(mm)	Part-Number	Contacts	Cable Range(mm)	Part-Number
	2	max7.2	21002223-01-XXX 	2	max7.2	21002213-01-XXX 
	3	max7.2	21003223-01-XXX 	3	max7.2	21003213-01-XXX 
	4(5A)	max7.2	21004223-01-XXX	4(5A)	max7.2	21004213-01-XXX
	4(2A)	max7.2	21004223-02-XXX	4(2A)	max7.2	21004213-02-XXX
	5	max7.2	21005223-01-XXX	5	max7.2	21005213-01-XXX
	6	max7.2	21006223-01-XXX	6	max7.2	21006213-01-XXX
	2+4	max7.2	21204223-01-XXX	2+4	max7.2	21204213-01-XXX
	7	max7.2	21007223-01-XXX	7	max7.2	21007213-01-XXX
	8	max7.2	21008223-01-XXX	8	max7.2	21008213-01-XXX

Specifications

Number of Contacts	2	3	4	4	5	6	2+4	7	8
Wire Gauge	20AWG				22AWG				
Cable Range	Max. 7.2mm								
Environmental Protection	IP67								
Mechanical Life	500 mating cycles								
Operating Temperature	- 40°C - 80°C								
Voltage Rating	110V	110V	110V	110V	50V	50V	50V	50V	50V
Rated Current(40°C)	5A	5A	5A	2A	2A	2A	5+2A	2A	2A

COMPANY PROFILE
500 Series
Mini Series
Standard Series
Middle Series
Large Series
Distributor Series
RJ45 Series
USB Series
D-Sub series
T Adapter Series
Splitter Series
HDMI Series
RJ45/12 CONN Series
M Series Distributor