







# STANDARD SERIES

## CHOGORI USA

### Standard Series Specifications

#### Standard Series, Male Connector & Female Pin

Description	Molded with Cable, 180° Screw Type, Solder	Molded with Cable, 180° Lock Bayonet Type, Solder	Molded with Cable, 180° Push Lock Type, Solder
Figure			

Drawing			
---------	---	--	---

Part Number	Contacts	Cable Range(mm)	Part Number	Contacts	Cable Range(mm)	Part Number	Contacts	Cable Range(mm)	Part Number
	2	Max. 9.0	22002213-01-XXX	2	Max. 9.0	22002223-01-XXX	2	Max. 9.0	22002233-01-XXX
	3	Max. 9.0	22003213-01-XXX	3	Max. 9.0	22003223-01-XXX	3	Max. 9.0	22003233-01-XXX
	4	Max. 9.0	22004213-01-XXX	4	Max. 9.0	22004223-01-XXX	4	Max. 9.0	22004233-01-XXX
	5	Max. 9.0	22005213-01-XXX	5	Max. 9.0	22005223-01-XXX	5	Max. 9.0	22005233-01-XXX
	6	Max. 9.0	22006213-01-XXX	6	Max. 9.0	22006223-01-XXX	6	Max. 9.0	22006233-01-XXX
	2+4	Max. 9.0	22204213-01-XXX	2+4	Max. 9.0	22204223-01-XXX	2+4	Max. 9.0	22204233-01-XXX
	3+4	Max. 9.0	22304213-01-XXX	3+4	Max. 9.0	22304223-01-XXX	3+4	Max. 9.0	22304233-01-XXX
	8	Max. 9.0	22008213-01-XXX	8	Max. 9.0	22008223-01-XXX	8	Max. 9.0	22008233-01-XXX
	10	Max. 9.0	22010213-01-XXX	10	Max. 9.0	22010223-01-XXX	10	Max. 9.0	22010233-01-XXX
	12	Max. 9.0	22012213-01-XXX	12	Max. 9.0	22012223-01-XXX	12	Max. 9.0	22012233-01-XXX

Specifications											
Number of Contacts	2	3	4	5	6	2+4	3+4	8	10	12	
Wire Gauge	18AWG			20AWG		18AWG*2C/3C 20AWG*4C		20AWG	22AWG		
Cable Range	Max. 9.0 mm										
Environmental Protection	IP67				IP67				IP67		
Mechanical Life	500 mating cycles										
Operating Temperature	- 40°C - 80°C										
Voltage Rating	300V	300V	125V	60V	60V	60V	60V	60V	30V	30V	
Rated Current (40°C)	10A	10A	10A	5A	5A	10A+5A	10A+2A	5A	2A	2A	