







# STANDARD SERIES

## CHOGORI

### Standard Series Specifications

#### Standard series, Male connector & Male Pin

Description	Molded with Cable, 90° Screw Type, Solder	Molded with Cable, 90° Lock Bayonet Type, Solder	Molded with Cable, 90° Push Lock Type, Solder
Figure			

Drawing			
---------	---	---	---

Part Number	Contacts	Cable Range(mm)	Part Number			Contacts	Cable Range(mm)	Part Number		
			Contacts	Cable Range(mm)	Part Number			Contacts	Cable Range(mm)	Part Number
	2	Max. 9.0	22002114-01-XXX	Max. 9.0	22002124-01-XXX	2	Max. 9.0	22002134-01-XXX		
	3		2200311401-XXX		22003124-01-XXX	3		22003134-01-XXX		
	4		22004114-01-XXX		22004124-01-XXX	4		22004134-01-XXX		
	5		22005114-01-XXX		22005124-01-XXX	5		22005134-01-XXX		
	6		22006114-01-XXX		22006124-01-XXX	6		22006134-01-XXX		
	2+4		22204114-01-XXX		22204124-01-XXX	2+4		22204134-01-XXX		
	2+6		22206114-01-XXX		22206124-01-XXX	2+6		22206134-01-XXX		

#### Specifications

Number of Contacts	2	3	4	5	6	2+4	2+6
Wire Gauge	0.823mm <sup>2</sup> (18AWG)			0.519mm <sup>2</sup> (20AWG)		0.823mm <sup>2</sup> (18AWG)*2C 0.34mm <sup>2</sup> (22AWG)*4C	
Cable Range	Max. 9.0 mm						
Environmental Protection	IP67			IP67			IP67
Mechanical Life	500 mating cycles						
Operating Temperature	- 40°C - 80°C						
Voltage Rating	300V	300V	125V	60V	60V	60V	30V
Rated Current (40°C)	10A	10A	10A	5A	5A	10A+2A	5A+2A